

new

STRATAS.MB



Xicato XTM LED (CRI = 98) spotlight / wall washer

luminaire

- small construction-kit spotlight system Ø 60mm
- with changeable optics

lamp

- XICATO / XTM Artist (CRI = 98 / R9=95)
Xicato XTM module 19mm
MB-XTM-19, 1300lm, typ. 16W
- colour temperature: 3000 K (2700 K, 3500 K, 4000 K on request)
1x2 step MacAdam initial.
- life hours: 50,000 h - L70/B0/F0
- Colour and lumen consistent over life
- other Xicato-LEDs and **2000lm** on request

beam angle

- 30° / 33° / 43° / 60° / wallwasher
- toolless exchange of lenses and wall washer front

accessoires

- wall washer front angled
- honey comb
- snoot
- diffusor
- sculpture lens
- barn doors

control

- XTM
 - potentiometer / 10-100% dimming
 - potentiometer / flicker free / 0,1-100% dimming
 - DALI / flicker free / 0,1-100% dimming
 - DALI + potentiometer / flicker free / 0,1-100% dimming

mounting

- track adapter 230V
(EUTRAC / STUCCHI 3-phase multiadapter with data option)
- surface mount (Ø=70, h=35) or recessed

orientation



- 0° - 90° vertical tilt and 360° rotation.

material / colour

- aluminium, powder coated
- white, silver, black (other colours available on request)

miscellaneous

- system typ. 17W
- Operating temperature: -25°C to 35°C
- weight: 0,6 kg



Xicato XTM LED (CRI = 98) Strahler / Wallwasher

Leuchte

- kleiner Baukasten-Systemstrahler Ø 60mm
- mit Wechseloptiken

Lampe

- XICATO / XTM Artist (CRI = 98 / R9=95)
Xicato XTM-Modul LES 19mm,
MB-XTM-19, 1300lm, typ. 16W
- Lichtfarbe: 3000 K (2700 K, 3500 K, 4000 K auf Anfrage)
in 1x2 MacAdam Basis
- Lebensdauer: 50,000 h - L70/B0/F0
- Farbe und Licht konstant während der gesamten Lebensdauer
- andere Xicato-LEDs und **2000lm** auf Anfrage

Ausstrahlwinkel

- 30° / 33° / 43° / 60° / Wallwasher
- werkzeugloser Austausch von Linsen und Wallwasher-Vorsatz

Zubehör

- Wallwasher-Vorsatz abgeschrägt
- Wabenraster
- Schute
- Diffusor
- Skulpturenlinse
- Blendklappen

Steuerung

- XTM
 - Potentiometer / 10-100% Dimmung
 - Potentiometer / flickerfrei / 0,1-100% Dimmung
 - DALI / flickerfrei / 0,1-100% Dimmung
 - DALI + Potentiometer / flickerfrei / 0,1-100% Dimmung

Montage

- Stromschienenadapter 230V
(EUTRAC / STUCCHI 3-Phasen Multiadapter mit Datenoption)
- Aufbau- (Ø=70, h=35) oder Einbauvariante

Ausrichtung

- 0° - 90° Schwenkbereich und 360° Drehung

Material / Farbe

- Aluminium, pulverbeschichtet
- weiß, silber, schwarz (weitere Farben auf Anfrage)

Sonstiges

- Systemleistung typ. 17W
- Betriebstemperatur -25°C bis 35°C
- Gewicht: 0,6 kg

