

new

# STRATAS.MB profile



# MB profile

960 lm
Ø 60 mm
beamshaper
XTM 9 mm LES

## Xicato XTM LED (CRI = 98) profile

### luminaire

- small construction-kit spotlight system Ø 60mm
- beamshaper

### lamp

- XICATO / XTM Artist (CRI = 98 / R9=95)  
Xicato XTM-module LES 9mm  
**MBp-XTM-9, 960lm, typ. 16W**
- colour temperature: 3000 K (2700 K, 3500 K, 4000 K on request)  
1x2 step MacAdam initial.
- life hours: 50,000 h - L70/B0/F0
- Colour and lumen consistent over life
- other Xicato-LEDs on request

### beam angle

- beamshaper

### accessoires

- snoot

### control

- XTM
  - potentiometer / 10-100% dimming
  - potentiometer / flicker free / 0,1-100% dimming
  - DALI / flicker free / 0,1-100% dimming
  - DALI + potentiometer / flicker free / 0,1-100% dimming

### mounting

- track adapter 230V  
(EUTRAC / STUCCHI 3-phase multiadapter with data option)
- surface mount (Ø=70, h=35) or recessed

### orientation

- 0°- 90° vertical tilt and 360° rotation.

### material / colour

- aluminium, powder coated
- white, silver, black (other colours available on request)



### miscellaneous

- system typ. 17W
- Operating temperature: -25°C to 35°C
- weight: 0,6 kg



illuminance E (lx)  
max. square edge length A (m)  
distance H (m)

H (m)	E (lx)	A (m)
2m	500 lx	0,6 m
3m	222 lx	0,9 m
4m	125 lx	1,2 m
6m	55 lx	1,8 m
8m	31 lx	2,4 m



# MB profile

960 lm
Ø 60 mm
beamshaper
XTM 9 mm LES

## Xicato XTM LED (CRI = 98) Beamshaper

### Leuchte

- kleiner Baukasten-Systemstrahler Ø 60mm
- Beamshaper

### Lampe

- XICATO / XTM Artist (CRI = 98 / R9=95)  
Xicato XTM-Modul LES 9mm  
**MBp-XTM-9, 960lm, typ. 16W**
- Lichtfarbe: 3000 K (2700 K, 3500 K, 4000 K auf Anfrage)  
in 1x2 MacAdam Basis
- Lebensdauer: 50,000 h - L70/B0/F0
- Farbe und Licht konstant während der gesamten Lebensdauer
- andere Xicato-LEDs auf Anfrage

### Ausstrahlwinkel

- Beamshaper

### Zubehör

- Schute

### Steuerung

- XTM
  - Potentiometer / 10-100% Dimmung
  - Potentiometer / flickerfrei / 0,1-100% Dimmung
  - DALI / flickerfrei / 0,1-100% Dimmung
  - DALI + Potentiometer / flickerfrei / 0,1-100% Dimmung

### Montage

- Stromschieneadapter 230V  
(EUTRAC / STUCCHI 3-Phasen Multi-adapter mit Datenoption)
- Aufbau- (Ø=70, h=35) oder Einbauvariante

### Ausrichtung

- 0° - 90° Schwenkbereich und 360° Drehung

### Material / Farbe

- Aluminium, pulverbeschichtet
- weiß, silber, schwarz (weitere Farben auf Anfrage)

### Sonstiges

- Systemleitung typ. 17W
- Betriebstemperatur -25°C bis 35°C
- Gewicht: 0,6 kg



Beleuchtungsstärken E (lx)  
max. quadratische Kantenlänge A (m)  
Entfernung H (m)

H (m)	E (lx)	A (m)
2m	500 lx	0,6 m
3m	222 lx	0,9 m
4m	125 lx	1,2 m
6m	55 lx	1,8 m
8m	31 lx	2,4 m

