

new

STRATAS.NV64 profile



NV64 profile

1050 lm
Ø 64 mm
beamshaper
XIM 9 mm LES

Xicato XIM LED (CRI = 98) profile

luminaire

- small construction-kit spotlight system Ø 64mm
- beamshaper

lamp

- XICATO / XIM-Artist (CRI = 98 / R9=95)
Xicato Module LES 9mm,
NV64p-XIM-9, 1050lm, typ. 22W
- colour temperature: 3000 K (2700 K, 3500 K, 4000 K on request)
1x2 step MacAdam initial.
- life hours: 50,000 h – L70/B0/F0
- Colour and lumen consistent over life
- other Xicato-LEDs on request

beam angle

- beamshaper

accessoires

- snoot

control

- XIM with Bluetooth low Energie (BLE)
- BLE / flicker free / 0,1-100% dimming / dimming control with iOS
or Android app
- DALI / flicker free / 0,1-100% dimming

mounting

- track adapter 48V DALI / EUTRAC
- surface mount

orientation

- 0° - 90° vertical tilt and 360° rotation.

material / colour

- aluminium, powder coated
- white, silver, black (other colours available on request)



miscellaneous

- system typ. 22W
- Operating temperature: -25°C to 35°C
- weight: 0,6 kg



illuminance E (lx)
max. square edge length A (m)
distance H (m)

H (m)	E (lx)	A (m)
2m	550 lx	0,6 m
3m	244 lx	0,9 m
4m	137 lx	1,2 m
6m	61 lx	1,8 m
8m	34 lx	2,4 m



NV64 profile

1050 lm
Ø 64 mm
beamshaper
XIM 9 mm LES

Xicato XIM LED (CRI = 98) Beamshaper für 48V Stromschiene mit Bluetooth (BLE) und DALI und 0-10V

Leuchte

- Baukasten-Systemstrahler Ø 64mm, für 48V Stromschiene
- Beamshaper

Lampe

- XICATO / XIM-Artist, (CRI = 98 / R9=95), Xicato XIM-Modul LES 9mm, **NV64p-XIM-9, 1050lm, typ. 22W**
- Lichtfarbe: 3000 K (2700 K, 3500 K, 4000 K auf Anfrage) in 1x2 MacAdam Basis
- Lebensdauer: 50,000 h – L70/B0/F0
- Farbe und Licht konstant während der gesamten Lebensdauer
- andere Xicato-LEDs auf Anfrage

Ausstrahlwinkel

- Beamshaper

Zubehör

- Schute

Steuerung

- XIM mit Bluetooth low Energie (BLE)
 - BLE / flickerfrei / 0,1-100% Dimmung / Steuerung mit iOS oder Android App
 - DALI / flickerfrei / 0,1-100% Dimmung

Montage

- Stromschiennenadapter 48V DALI / EUTRAC
- Aufbauvariante

Ausrichtung

- 0°- 90° Schwenkbereich und 360° Drehung

Material / Farbe

- Aluminium, pulverbeschichtet
- weiß, silber, schwarz (weitere Farben auf Anfrage)

Sonstiges

- Systemleistung typ. 22W
- Betriebstemperatur -25°C bis 35°C
- Gewicht: 0,6 kg



Beleuchtungsstärken E (lx)
max. quadratische Kantenlänge A (m)
Entfernung H (m)

H (m)	E (lx)	A (m)
2m	550 lx	0,6 m
3m	244 lx	0,9 m
4m	137 lx	1,2 m
6m	61 lx	1,8 m
8m	34 lx	2,4 m

