

new

# STRATAS.NV64 zoom



# NV64 zoom

1050 lm
Ø 64 mm
14° - 53° zoom
XIM 9 mm LES

## Xicato XIM LED (CRI = 98) zoom-spotlight for 48V track with Bluetooth (BLE) and dali-control

### luminaire

- small construction-kit spotlight system Ø 64mm
- with zoom-optic

### lamp

- XICATO / XIM-Artist (CRI = 98 / R9=95)  
Xicato Module LES 9mm,  
**NV64z-XIM-9, 1050lm, typ. 22W**
- colour temperature: 3000 K (2700 K, 3500 K, 4000 K on request)  
1x2 step MacAdam initial.
- life hours: 50,000 h – L70/B0/F0
- Colour and lumen consistent over life
- other Xicato-LEDs on request

### beam angle

- zoomlens 14°-53°

### accessoires

- snoot
- diffusor
- sculpture lens

### control

- XIM with Bluetooth low Energie (BLE)
  - BLE / flicker free / 0,1-100% dimming / dimming control with iOS or Android app
  - DALI / flicker free / 0,1-100% dimming

### mounting

- track adapter 48V DALI / EUTRAC
- surface mount

### orientation



- 0° - 90° vertical tilt and 360° rotation.

### material / colour

- aluminium, powder coated
- white, silver, black (other colours available on request)

### miscellaneous

- system typ. 22W
- Operating temperature: -25°C to 35°C
- weight: 0,6 kg



## NV64 zoom

1050 lm
Ø 64 mm
14° - 53° zoom
XIM 9 mm LES

### Xicato XIM LED (CRI = 98) Zoom-Strahler für 48V Stromschiene mit Bluetooth (BLE) und DALI und 0-10V

#### Leuchte

- Baukasten-Systemstrahler Ø 80mm, mit kurzem Leuchtenkopf für 48V Stromschiene
- Zoom-Optik

#### Lampe

- XICATO / XIM-Artist, (CRI = 98 / R9=95), Xicato XIM-Modul LES 9mm,  
**NV64z-XIM-9, 1050lm, typ. 22W**
- Lichtfarbe: 3000 K (2700 K, 3500 K, 4000 K auf Anfrage) in 1x2 MacAdam Basis
- Lebensdauer: 50,000 h – L70/B0/F0
- Farbe und Licht konstant während der gesamten Lebensdauer
- andere Xicato-LEDs auf Anfrage

#### Ausstrahlwinkel

- Zoomlinsenvorsatz 14°-53°

#### Zubehör

- Schute
- Diffusor
- Skulpturenlinse

#### Steuerung

- XIM mit Bluetooth low Energie (BLE)
  - BLE / flickerfrei / 0,1-100% Dimmung / Steuerung mit iOS oder Android App
  - DALI / flickerfrei / 0,1-100% Dimmung

#### Montage

- Stromschienenadapter 48V DALI / EUTRAC
- Aufbauvariante

#### Ausrichtung

- 0° - 90° Schwenkbereich und 360° Drehung

#### Material / Farbe

- Aluminium, pulverbeschichtet
- weiß, silber, schwarz (weitere Farben auf Anfrage)

#### Sonstiges

- Systemleistung typ. 22W
- Betriebstemperatur -25°C bis 35°C
- Gewicht: 0,6 kg

