

new

STRATAS.NV80



NV80

1750-2250 lm

Ø 80 mm

spot / ww

XIM 19 mm LES

Xicato XIM LED (CRI = 98) spotlight / wallwasher for 48V track and Bluetooth (BLE) and dalicontrol and 0-10V

luminaire

- small construction-kit spotlight system Ø 80mm, with short luminaire body, for 48V track
- with changeable optics

lamp

- XICATO / XIM-Artist (CRI = 98 / R9=95)
Xicato module LES 19mm,
NV80-XIM-19, 1750 lm, typ. 25W
NV80-XIM2-19, 2250 lm, typ 23W
- colour temperature: 3000 K (2700 K, 3500 K, 4000 K on request)
1x2 step MacAdam initial.
- life hours: 50,000 h – L70/B0/F0
- Colour and lumen consistent over life
- other Xicato-LEDs on request

beam angle

- 20° / 25° / 38° / 60° / wallwasher
- toolless exchange of lenses and wall washer front

accessoires

- wallwasher front angled
- snoot
- diffusor
- sculpture lens
- barn doors

control

- XIM with Bluetooth low Energie (BLE)
 - BLE + potentiometer / flicker free / 0,1-100% dimming / dimming control with iOS or Android app
 - BLE / flicker free / 0,1-100% dimming / dimming control with iOS or Android app
 - DALI / flicker free / 0,1-100% dimming

mounting

- track adapter 48V DALI / EUTRAC
- surface mount

orientation



- 0° - 90° vertical tilt and 360° rotation.

material / colour

- aluminium, powder coated
- white, silver, black (other colours available on request)

miscellaneous

- system typ. 25W / 23W
- Operating temperature: -25°C to 35°C
- weight: 0,6 kg



NV80

1750-2250 lm

Ø 80 mm

spot / ww

XIM 19 mm LES

Xicato XIM LED (CRI = 98)

Strahler / Wallwasher für 48V Stromschiene mit Bluetooth (BLE) und DALI und 0-10V

Leuchte

- Baukasten-Systemstrahler Ø 80mm, mit kurzem Leuchtenkopf für 48V Stromschiene
- mit Wechselloptiken

Lampe

- XICATO / XIM-Artist
Xicato XIM-Modul LES 19mm, (CRI = 98 / R9=95),
NV80-XIM-19, 1750 lm, typ. 25W
NV80-XIM2-19, 2250 lm, typ 23W
- Lichtfarbe: 3000 K (2700 K, 3500 K, 4000 K auf Anfrage)
in 1x2 MacAdam Basis
- Lebensdauer: 50,000 h - L70/B0/F0
- Farbe und Licht konstant während der gesamten Lebensdauer
- andere Xicato-LEDs auf Anfrage

Ausstrahlwinkel

- 20° / 25° / 38° / 60° / Wallwasher
- werkzeugloser Austausch von Linsen und Wallwasher-Vorsatz

Zubehör

- Wallwasher-Vorsatz abgeschrägt
- Blendklappen
- Schute
- Diffusor
- Skulpturenlinse

Steuerung

- XIM mit Bluetooth low Energie (BLE)
 - BLE + Potentiometer / flickerfrei / 0,1-100% Dimmung / Steuerung mit iOS oder Android App
 - BLE / flickerfrei / 0,1-100% Dimmung / Steuerung mit iOS oder Android App
 - DALI / flickerfrei / 0,1-100% Dimmung

Montage

- Stromschienenadapter 48V DALI / EUTRAC
- Aufbauvariante

Ausrichtung

- 0° - 90° Schwenkbereich und 360° Drehung

Material / Farbe

- Aluminium, pulverbeschichtet
- weiß, silber, schwarz (weitere Farben auf Anfrage)

Sonstiges

- Systemleistung typ. 25W / 23W
- Betriebstemperatur -25°C bis 35°C
- Gewicht: 0,6 kg

